

# Luceplan

## Counterbalance Floor



### Technical details

<b>Country of Manufacture</b>	 Italy
<b>Manufacturer</b>	Luceplan
<b>Designer</b>	Paolo Rizzatto
<b>Year of design</b>	2015
<b>protection</b>	IP20
<b>Scope of delivery</b>	LED
<b>voltage suitability</b>	110 - 240 Volt
<b>material</b>	aluminum, steel, zinc
<b>surface</b>	black
<b>dimming</b>	Cord dimmer with slider
<b>switchability</b>	on the light head
<b>Wattage</b>	16 W
<b>LED</b>	inclusive
<b>Colour Rendering Index</b>	90
<b>Luminous flux in lm</b>	598
<b>Color temperature in Kelvin</b>	2,700 extra warm white
<b>Shade diameter</b>	9 cm
<b>lamp stand dimensions</b>	15 cm
<b>Dimensions</b>	H 170 cm

### Description

The Luceplan Counterbalance Floor has a rotating and traversable head. In addition, the lamp head can be adjusted at any time along the rod in its height. For this, neither screws nor other complicated handles have to be carried out. As a result, the light can also be used as a reading light. The lampshade, rod and base are all black. There is a dimmer included on the cable with which the light intensity can be dimmed. On the lamp head an on and off switch is placed. The light collection won the Compasso d'Oro ADI in the year 2014. Daniel Rybakken designed the collection for Luceplan.