



Technical details

Country of Manufacture 💻 Germany Manufacturer less'n'more Designer less'n'more protection IP43 Scope of delivery LED voltage suitability 110 - 240 Volt material aluminum, concrete, leather beam angle 50 - 100 degrees cable color transparent cable length 200 cm height adjustment height adjustable dimming Rotary dimmer on head Wattage 12.6 W LED inclusive 95 **Colour Rendering Index** Luminous flux in lm 1,200 Color temperature in Kelvin 2,700 extra warm white lamp stand dimensions 23 cm light head dimensions 9 cm bulb exchange on site itself light distribution directly Dimensions H 87 - 137 cm

less'n'more Ylux Floor Light

Leuchtenkopf

- polished aluminum
- matt white
- black matt

Description

The Less'n'more Ylux floor lamp is a single-flame floor lamp with a rotating and swiveling lamp head. To change the beam angle of the light, the glass lens is rotated in or out of the luminaire head. With a larger beam angle, the light is distributed over a larger area. With this luminaire, the beam angle can be adjusted between 50 and 100 degrees.

The luminaire head is available in different colors. The luminaire in polished aluminum and in black has a grey luminaire base, the luminaire with white luminaire head has a white luminaire base.

The light rod of the floor lamp consists of an aluminum telescopic tube. A leather loop is used for easy height adjustment. The height of the light can be adjusted as required between 87 cm and 137 cm. The Ylux floor lamp has several smooth-running ball joints that allow the light rod on the base to tilt 20° and the head to swivel 135° and rotate 360°.

The concrete base has a diameter of 23 cm and has a cable reel. Due to the natural nature of the material, the surfaces of the luminaire base may vary, i.e. be lighter/darker. An LED is integrated as the light source for the Ylux floor lamp. The brightness of the light can be adjusted using a rotary dimmer on the light head.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@wawawu.de