



# Ingo Maurer

## Luce Volante


### Oberfläche

- gold
- red
- white

### Version

- with driver
- without driver

## Technical details

|                                    |   |
|------------------------------------|---|
| <b>Country of Manufacture</b>      |  Germany |
| <b>Manufacturer</b>                | Ingo Maurer   |
| <b>Designer</b>                    | Ingo Maurer   |
| <b>Year of design</b>              | 2018  |
| <b>protection</b>                  | IP20  |
| <b>Scope of delivery</b>           | LED   |
| <b>voltage suitability</b>         | 110 - 240 Volt  |
| <b>material</b>                    | aluminum, glass fiber   |
| <b>cable length</b>                | 400 cm  |
| <b>height adjustment</b>           | height determinable   |
| <b>dimming</b>                     | on site dimmable with a trailing edge dimmer  |
| <b>Wattage</b>                     | 23 W  |
| <b>LED</b>                         | inclusive   |
| <b>Colour Rendering Index</b>      | 95  |
| <b>Color temperature in Kelvin</b> | Dim to warm   |
| <b>bulb exchange</b>               | on site itself  |
| <b>Total luminous flux in lm</b>   | 2,300   |
| <b>light distribution</b>          | directly and indirectly   |
| <b>Dimensions</b>                  | B 30 cm   L 145 cm  |

## Description

The Ingo Maurer Luce Volante pendant lamp serves simultaneously as uplight and downlight. The majority of the light is emitted downwards. By using dim-to-warm technology, the colour temperature of the integrated LEDs changes from 1,800 Kelvin extra warm white to 3,000 Kelvin warm white during dimming. The light body is 145 cm long and 30 cm wide. The Luce Volante is available in white matt, gold or red matt finishes. It is also offered in special colours on request. This pendant lamp is available with and without driver. If required, the cables can be shortened.