

less'n'more

Zeus Wall Light Z-BWL1

Dimmbarkeit

- Push button dimmer on the wall bracket
- on site dimmable with a trailing edge dimmer

Oberfläche

- aluminum
- black
- white

flexible arm

- textile white
- textile black
- textile blue
- · textile anthracite
- aluminum
- textile green
- textile red
- textile brown

Description

The Less'n'more Zeus Wall Light Z-BWL1 is mounted on the wall as standard, but is also suitable for mounting on a flush-mounted box. Its wall bracket / mounting plate has a diameter of 10 cm and can be mounted freely by 360 degrees. The flexible lamp arm can be stretched and bent as desired. At maximum extension of the lamp arm, the lamp has a height of 30 cm. The flexible lamp arm is available in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

Lamp head and wall bracket are offered in the surfaces aluminum and black. The beam angle of the light can be adjusted continuously between 15 and 75 degrees. To do this, the glass lens is turned out of or into the lamp head. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated in the lamp head.

The Zeus Wall Light Z-BWL1 is offered on site dimmable with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. Its flexible lamp arm is available in other colours on request. The Zeus wall lamp is also offered on request with supply cable and safety plug in order to be connected directly to a power supply. In addition to this lamp, there is also available the larger Zeus Wall Light Z-BWL2 with a maximum height of 61 cm.

Technical details

Country of Manufacture

Manufacturer

Designer

Year of design

protection

Scope of delivery

Germany

Germany

2021

1P43

LED

voltage suitability230 - 240 Voltmaterialaluminum, glassbeam angle15 - 75 degrees

Wattage 4.2 W
LED inclusive
Colour Rendering Index 90
Luminous flux in Im 450

Color temperature in Kelvin 2,700 extra warm white

light head dimensions 3 cm
bulb exchange on site itself
Wall mount dimensions 10 cm
Dimensions H max. 30 cm