



B.Lux

Lite Hole C/W 60

Oberfläche

- copper
- black
- gold
- white

Technical details

| | |
|------------------------------------|---|
| Country of Manufacture |  Spain |
| Manufacturer | B.Lux |
| Designer | David Abad |
| protection | IP20 |
| Scope of delivery | LED |
| voltage suitability | 230 - 240 Volt |
| Diameter in cm | 60 |
| material | acrylic glass, aluminum |
| dimming | push dimmable |
| Wattage | 17.4 W |
| LED | inclusive |
| Colour Rendering Index | >90 |
| Luminous flux in lm | 3,416 |
| Color temperature in Kelvin | 3,000 warm white |
| Dimensions | H 8 cm Ø 60 cm |

Description

The B.Lux Lite Hole C/W 60 ceiling light consists of two concentric aluminum rings that sit on top of each other. Its lamp body has a diameter of 60 cm and a height of 6 cm. Including the ceiling bracket, this lamp is 8 cm high. A diffuser made of opal white acrylic glass prevents any glare and distributes the light homogeneously downwards.

The Lite Hole C/W 60 is available in white matt, black matt, copper and gold. The integrated, powerful LED has a colour temperature of 3,000 Kelvin warm white and an output of 17.4 watts. It can be dimmed with Push or DALI. Push requires a 4-core mains lead for dimming, DALI a 5-core. A version that can be dimmed with a Casambi module by smartphone via Bluetooth is also available on request. The version with Casambi module can be operated easily and intuitively via mobile devices with the free CASAMBI app (iOS and Android). Casambi thus expands the control options with functions such as dimming, grouping of lamps, programming of groups and scenes, automations and much more. In addition to this ceiling light, the Lite Hole is also available with a diameter of 90 cm or 120 cm.