

B.Lux

Lite Hole C/W 120

Oberfläche

- copper
- black
- gold
- white

Technical details

Country of Manufacture

Manufacturer

B.Lux

Designer

David Abad

protection

IP20

Scope of delivery LED

voltage suitability 230 - 240 Volt

Diameter in cm 120

materialacrylic glass, aluminumdimmingpush dimmable

LED inclusive
Colour Rendering Index >90

Color temperature in Kelvin 3,000 warm white

system performance 1 x 19.5 Watt + 1 x 41 Watt

Total luminous flux in lm 11,624

Dimensions H 8 cm \mid Ø 120 cm

Description

The B.Lux Lite Hole C/W 120 ceiling light consists of two concentric aluminum rings that sit on top of each other. Its lamp body has a diameter of 120 cm and a height of 6 cm. Including the ceiling bracket, this lamp is 8 cm high. Thanks to a diffuser made of opal white acrylic glass, any glare is prevented and the light is homogeneously distributed downwards.

The Lite Hole C/W 120 is available in the surfaces white matt, black matt, copper and gold. The two integrated LEDs each have a colour temperature of 3,000 Kelvin warm white. One of the two LEDs has an output of 19.5 watts, the other 41 watts. The ceiling light can be dimmed with Push or DALI. Push requires a 4-wire mains supply line for dimming, DALI a 5-wire. A version that can be dimmed with a Casambi module by smartphone via Bluetooth is also available on request. The version with Casambi module can be operated easily and intuitively via mobile devices with the free CASAMBI app (iOS and Android). Casambi thus expands the control options with functions such as dimming, grouping of lamps, programming of groups and scenes, automations and much more. In addition to this ceiling light, the Lite Hole is also offered with a diameter of 60 cm or 90 cm.