

Knapstein

HELLI-1

Oberfläche

- nickel
- black
- bronze

Struktur#

- nickel
- black
- bronze

Technical details

Country of Manufacture Germany

Manufacturer Knapstein

Year of design 2023 Diameter in cm 8

material

height adjustment height adjustable dimming gesture control

Wattage 2x8 W

LED # inclusive

Colour Rendering Index >90

Luminous flux in Im 2140

Color temperature in Kelvin 2.700 extra warm white

protection IP20 Scope of delivery LED

voltage suitability 230 - 240 Volt

canopy Ø9cr

bulb exchange at the manufacturer / at the factory

Acryl, Metall

 total height
 70 - 170 cm

 Dimensions
 Ø 8 cm

Description

The Knapstein HELLI-1 LED pendant lamp has a cylindrical lamp body with freely combinable structures on the underside of the luminaire. The glass of the lower diffuser of the luminaire is reversible, making it easy to choose between a lens for a focussed lighting effect and a disc for a diffuse lighting effect. To do this, unscrew the lower light ring and place the enclosed glass in the desired position (lens/disc). The aforementioned screw ring (structure) is available in 3 different colours. A swiping hand movement in the sensor area switches the corresponding light source on or off. To dim the light, the hand is held in front of the respective sensor until the desired light intensity is reached. Thanks to the integrated memory function, the last settings are saved and are immediately available again the next time the light is switched on. The uplight and downlight can be switched and dimmed separately using gesture control. With the built-in lift height adjustment, the luminaire height can be continuously adjusted from approx. 70 cm - 170 cm. The Knapstein HELLI-1 has a synchronisation function for adjusting the light intensity of all light sources on one side of the luminaire. The ceiling canopy of the Knapstein HELLI-1 LED pendant lamp has a magnetic holder, so no external screw connections are visible. This pendant lamp is available in several surfaces and freely combinable external structures on the underside.