




Mawa

Wittenberg 4.0 ceiling lamp Downlight LED

Oberfläche

- negro
- blanco

Technical details

País de la Fabricación	 Alemania
fabricante	Mawa
diseñador	Jan Dinnebier
diseñador 2	mawa engineering
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
Diámetro en cm	8
material	aluminio, metal
ángulo del rayo	38 grados
Atenuación	dimnable con control de fase inversa y con reguladores de control de fase
Potencia en vatios	12,7 W
LED	incluyendo
Índice de reproducción cromática	95
El flujo luminoso en lm	1.100
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
reemplazo de la bombilla:	en el sitio mismo
distribución de la luz	directamente
Dimensions	H 12 cm Ø 8 cm

Descripción

The Mawa Wittenberg 4.0 ceiling lamp Downlight LED emits its light directly and bundled downwards. Neither screws nor cables are visible in the compact design of the lamp. This lamp has a height of 11.5 cm and a diameter of 7.6 cm. An LED is integrated as a light source, which can be dimmed by the customer with a leading or trailing edge phase dimmer. On request, the lamp is also available as a DALI or 1-10 volt dimmable version. These two optionally available versions (DALI or 1-10 Volt) then have a height of 14.7 cm with a diameter of 7.6 cm. The Wittenberg 4.0 ceiling lamp Downlight LED is available with powder-coated black matt or white matt surfaces. The integrated LED has a colour temperature of 2,700 Kelvin extra warm white. On request it is also offered with 3,000 Kelvin warm white or 4,000 Kelvin white.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.