

# Cini & Nils

# Acqua with double canopy

### Oberfläche

- oro
- plata
- blanco

#### Version

- Downlight
- Uplight

### **Technical details**

País de la Fabricación **Italia** fabricante Cini & Nils diseñador Luta Bettonica

año 2014 protección IP20 Volumen de suministro LED

entrada de tensión 230 - 240 Volt material acero, aluminio ajuste de altura altura determinada

con un regulador de intensidad integrado **Atenuación** y controlado por un interruptor

cm

3.250

5 x 5,6 Watt

2.800 blanco cálido

Longitud 33 cm, anchura 11 cm, altura 5

LED incluyendo

Indice de reproduccion

cromatica

Temperatura de color en

grados Kelvin

Dimensiones del dosel

El rendimiento del

sistema

Flujo total luminoso en

altura total 200 cm **Dimensions** H 86 cm

## Descripción

This Cini & Nils Acqua consists of two multiple lamps suspended next to each other on a canopy. A total of five lighting elements are integrated. The lamp is available in the surfaces white, silver matt and gold matt. On request it is also offered in silver leaf or gold leaf. The oval canopy is supplied in the matching surface to the lamp. The Acqua is offered in two versions: As an uplight it emits indirect light directed upwards and as a downlight it emits direct light directed downwards.

The pendant light with multiple canopy is operated with a switch-controlled, integrated dimmer, with which the light can be dimmed continuously via the normal light switch. No additional cables are required for this. The dimming function is activated by switching on and off once. The maximum light intensity is reached within seven seconds. To set the desired light intensity, switch on and off again. The set light intensity is saved via a memory function and automatically selected again when the light is switched on again. On request, the Acqua with double canopy is also available on site dimmable with Push.

This light has a total of five individual Acqua elements. On request, the pendant lamp is also available with up to ten elements. The pendant light has a maximum height of 200 cm, the cables can be shortened if required. A decentralisation kit is offered as an accessory, which allows the lamp to be installed independently of the power supply.