




# Knapstein

## ELSA-L

### Oberfläche

- latón
- níquel

### Technical details

<b>País de la Fabricación</b>	 Alemania
<b>fabricante</b>	Knapstein
<b>diseñador</b>	Knapstein
<b>protección</b>	IP20
<b>Volumen de suministro</b>	LED
<b>entrada de tensión</b>	230 - 240 Volt
<b>Proyección en cm</b>	57
<b>material</b>	latón, vidrio
<b>Atenuación</b>	Dimmer táctil en la varilla de la lámpara y dimmer táctil en el cabezal de la lámpara
<b>LED</b>	incluyendo
<b>Indice de reproducción cromática</b>	>90
<b>Temperatura de color en grados Kelvin</b>	2.700 extra blanco cálido
<b>Dimensiones del soporte de la lámpara</b>	28 cm
<b>El rendimiento del sistema</b>	1 x 28 Watt + 1 x 8,5 Watt
<b>Flujo total luminoso en lm</b>	5.215
<b>Dimensions</b>	H 185 cm

### Descripción

The Knapstein ELSA-L emits light upwards as a ceiling floodlight. The floor lamp also has a rotating and swivelling reading arm that can be realigned at any time. A further joint allows the lamp head on the reading arm to be swivelled independently of the arm. The uplight of the ceiling floodlight and the light of the lamp head can be switched separately and dimmed continuously via two push button dimmers. The push button dimmer for the uplight is integrated on the light rod. The push button dimmer for the light head is located on the head itself. The ELSA-L is available in the surfaces brass matt and nickel matt. The uplight has an opal, matt white glass. The floor lamp from Knapstein is also offered without reading arm.