




Knapstein

ELSA-L

Oberfläche

- latón
- níquel

Technical details

País de la Fabricación	 Alemania
fabricante	Knapstein
diseñador	Knapstein
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
Proyección en cm	57
material	latón, vidrio
Atenuación	Dimmer táctil en la varilla de la lámpara y dimmer táctil en el cabezal de la lámpara
LED	incluyendo
Indice de reproducción cromática	>90
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
Dimensiones del soporte de la lámpara	28 cm
El rendimiento del sistema	1 x 28 Watt + 1 x 8,5 Watt
Flujo total luminoso en lm	5.215
Dimensions	H 185 cm

Descripción

The Knapstein ELSA-L emits light upwards as a ceiling floodlight. The floor lamp also has a rotating and swivelling reading arm that can be realigned at any time. A further joint allows the lamp head on the reading arm to be swivelled independently of the arm. The uplight of the ceiling floodlight and the light of the lamp head can be switched separately and dimmed continuously via two push button dimmers. The push button dimmer for the uplight is integrated on the light rod. The push button dimmer for the light head is located on the head itself. The ELSA-L is available in the surfaces brass matt and nickel matt. The uplight has an opal, matt white glass. The floor lamp from Knapstein is also offered without reading arm.