




Catellani & Smith

Syphaduepassi Set 4

Technical details

| | |
|--|--|
| País de la Fabricación |  Italia |
| fabricante | Catellani & Smith |
| diseñador | Enzo Catellani |
| año | 2018 |
| protección | IP44 |
| Volumen de suministro | LED |
| entrada de tensión | 230 - 240 Volt |
| material | latón, vidrio |
| base/portalámparas | G4 |
| LED | incluyendo |
| Indice de reproduccion cromatica | 80 |
| Temperatura de color en grados Kelvin | 2.700 extra blanco cálido |
| reemplazo de la bombilla: | en el sitio mismo |
| El rendimiento del sistema | 4 x 1 Watt |
| Flujo total luminoso en lm | 300 |
| Dimensiones | H 2 x 45 + 2 x 75 cm |

Descripción

The Catellani & Smith Syphaduepassi Set 4 consists of four complete outdoor floor lamps, ready for connection, with all necessary accessories. The Syphaduepassi lamps can be easily connected to each other using the Catellani & Smith Quick Connectors system. Only a single power connection is required for installation. All necessary plug connections are included. Included in the set:

- Two lamps with a height of 45 cm
- two lamps with a height of 75 cm
- an extension cable with a length of 500 cm
- a driver necessary for lamp operation

The Syphaduepassi outdoor floor lamps can be fixed with their ground spike up to 25 cm into the ground. The heights of the lamps (45 cm and 75 cm) are indicated without ground spike. The light is focused and emitted without glare through the glass lenses of the lamps. The brass lamp rod of each lamp can be bent and realigned if necessary.

With IP44 protection, the Syphaduepassi lamps are protected against splashing water on all sides and solid foreign bodies with a diameter of 1 mm or more. With IP65 protection, the lamp rods are dust-tight and protected against strong jets of water from any angle. Drivers and extension cables are protected against temporary immersion with IP67 protection. The series also includes sets with one complete lamp or with two, three, five or nine complete lamps.