



Mawa

Seventies surface-mounted spot light LED dimmable


Oberfläche

- negro
- blanco

Farbtemperatur in Kelvin

- 2.700 extra blanco cálido
- 3.000 blanco cálido

Technical details

País de la Fabricación	 Alemania
fabricante	Mawa
diseñador	Jan Blieske
diseñador 2	Jan Dinnebier
año	2020
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
material	aluminio
ángulo del rayo	30 grados
Atenuación	Regulable en el sitio con control de fase inversa
Potencia en vatios	25 W
LED	incluyendo
Índice de reproducción cromática	>90
cabeza del alumbrado masa	9 cm
reemplazo de la bombilla:	en el fabricante / en la fabrica
Dimensions	H 22 cm

Descripción

The Mawa Seventies surface-mounted spotlight LED has a cylindrical lamp head that can be rotated by 365 degrees and swivelled by 90 degrees. Thanks to its compact design, the ceiling lamp has no visible screw connections. It is a total of 21.6 cm high and has a lamp head with a diameter of 9 cm. The surface-mounted spotlight is available in the powder-coated surfaces white or black matt. It is also available in other RAL colours on request.

The Seventies ceiling spotlight is available with a colour temperature of 2,700 Kelvin extra warm white or 3,000 Kelvin warm white. On request, it is also offered with 4,000 Kelvin white. This lamp can be dimmed on site with a trailing edge phase dimmer. DALI, 1-10 volt or rotary control versions are also available on request. The colour rendering index of the lamp is Ra >90. On request, it is also on offer with Ra >95, which is closer to natural light (Ra 100).

The Seventies surface-mounted spotlight LED has a beam angle of 30 degrees as standard. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 16 or 22 degrees in the field Order Comment.