



B.Lux Lite Hole C/W 120

Oberfläche

- cobre
- negro
- oro
- blanco

Technical details

País de la Fabricación	 España
fabricante	B.Lux
diseñador	David Abad
protección	IP20
Volumen de suministro	LED
entrada de tensión	230 - 240 Volt
Diámetro en cm	120
material	aluminio, vidrio acrílico
Atenuación	Empuje regulable
LED	incluyendo
Indice de reproduccion cromatica	>90
Temperatura de color en grados Kelvin	3.000 blanco cálido
El rendimiento del sistema	1 x 19,5 Watt + 1 x 41 Watt
Flujo total luminoso en lm	11.624
Dimensions	H 8 cm Ø 120 cm

Descripción

The B.Lux Lite Hole C/W 120 ceiling light consists of two concentric aluminum rings that sit on top of each other. Its lamp body has a diameter of 120 cm and a height of 6 cm. Including the ceiling bracket, this lamp is 8 cm high. Thanks to a diffuser made of opal white acrylic glass, any glare is prevented and the light is homogeneously distributed downwards.

The Lite Hole C/W 120 is available in the surfaces white matt, black matt, copper and gold. The two integrated LEDs each have a colour temperature of 3,000 Kelvin warm white. One of the two LEDs has an output of 19.5 watts, the other 41 watts. The ceiling light can be dimmed with Push or DALI. Push requires a 4-wire mains supply line for dimming, DALI a 5-wire. A version that can be dimmed with a Casambi module by smartphone via Bluetooth is also available on request. The version with Casambi module can be operated easily and intuitively via mobile devices with the free CASAMBI app (iOS and Android). Casambi thus expands the control options with functions such as dimming, grouping of lamps, programming of groups and scenes, automations and much more. In addition to this ceiling light, the Lite Hole is also offered with a diameter of 60 cm or 90 cm.