

# Byok

## Assiale L




### Dimmbarkeit

- dimmable DALI
- Capteur de lumière du jour et le mouvement

### Version

- pivotant
- fixé

## Technical details

<b>Pays de fabrication</b>	 Allemagne
<b>fabricant</b>	Byok
<b>concepteur</b>	Kai Byok
<b>protection</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>matériel</b>	aluminium
<b>Puissance (max. Watt)</b>	60 Watt
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	80
<b>La température de couleur en Kelvin</b>	3.000 blanc chaud
<b>Flux lumineux total en LM</b>	4400 lm ci-dessous 4400 lm ci-dessus
<b>répartition de la lumière</b>	directement et indirectement
<b>Dimensions</b>	H 48 cm   B 7 cm   L 180 cm

## Description

The Byok Assiale L is attached directly to the ceiling. It is available as fixed and rotatable. The joint of the rotating lamp is both flexible and robust. A spring-loaded mechanism protects the joint when the lamp is rotated.

The light is offered in anodized aluminum as well as on request powdered in RAL colours. The lamp is offered in three versions: on site DALI dimmable or controllable with light and motion sensors. It emits up- and downlight. In contrast to the Assiale T, this lamp has an L-shape.