

# Byok

## Assiale T



### Dimmbarkeit

- dimmable DALI
- Capteur de lumière du jour et le mouvement

### Version

- pivotant
- fixé

## Technical details

|  |   |
|--|---|
| <b>Pays de fabrication</b>                 |  Allemagne |
| <b>fabricant</b>                           | Byok  |
| <b>concepteur</b>                          | Kai Byok  |
| <b>protection</b>                          | IP20  |
| <b>Contenu de la livraison</b>             | LED   |
| <b>matériel</b>                            | aluminium   |
| <b>Puissance (max. Watt)</b>               | 120 Watt  |
| <b>LED</b>                                 | y compris   |
| <b>Indice de rendu des couleurs</b>        | 80  |
| <b>La température de couleur en Kelvin</b> | 3.000 blanc chaud   |
| <b>Flux lumineux total en LM</b>           | 2 x 4400 lm vers le bas, vers le haut<br>4400 2x lm   |
| <b>répartition de la lumière</b>           | directement et indirectement  |
| <b>Dimensions</b>                          | H 48 cm   B 7 cm   L 300 cm   |

## Description

The Byok Assiale T is the larger version of the two ceiling lights from the same family of lamps. It has in comparison to the smaller ASSIALE L a length of 300 cm compared to 180 cm of the L-version. Its surface is made of anodized aluminum, on request it is also offered in all RAL colours powdered.

The lighting is offered fixed or in a rotary version. The rotary version is protected against incorrect loading through its spring-loaded mechanism in the joint. Each version is offered in the different versions DALI dimmable or with daylight and motion sensor.