




# Florian Schulz

## Ova

### Version

- Laiton laqué bruni
- Laiton laqué bruni foncé
- Matt laiton brossé laqué
- Fini laiton poli
- Laiton poli sans laque
- laiton chromé
- laiton plaqué cuivre laqué
- laiton cuivré laqué mat brossé
- laiton nickelé
- laiton nickele laque
- Matt laiton brossé nickelé

### Technical details

<b>Pays de fabrication</b>	 Allemagne
<b>fabricant</b>	Florian Schulz
<b>concepteur</b>	Jens Schump
<b>année</b>	2017
<b>protection</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>aptitude de tension</b>	110 - 240 Volt
<b>matériel</b>	laiton
<b>réglage de la hauteur</b>	hauteur déterminée
<b>atténuation</b>	dimmerable sur place avec commande gradateur de phase inverse
<b>Puissance en Watt</b>	96 W
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	>95
<b>La température de couleur en Kelvin</b>	2.700 extra blanc chaud
<b>canopée Dimensions</b>	Largeur 47 cm, hauteur 5 cm
<b>Flux lumineux total en LM</b>	4.800
<b>répartition de la lumière</b>	directement et indirectement
<b>hauteur totale</b>	100 - 200 cm
<b>Dimensions</b>	H 4 cm   B 47 cm   L 125 cm

### Description

The VS Manufaktur Ova is a pendant lamp with an oval lamp body. The length of the lamp is 125 cm, it has a width of 47 cm. The lamp body is 4 cm high. The light is emitted both upwards and downwards. The Florian Schulz Ova is variably determinable in a height of 100 cm to 200 cm. On request, variants with different suspensions are also offered. An LED with a diffuser as well as an power of 60 watts and 2,700 Kelvin extra warm white is integrated. The pendant lamp is available in different surfaces: brass polished lacquered, nickel-plated, matt brushed lacquered, nickel-plated matt brushed, burnished lacquered, dark burnished lacquered, copper-plated, nickel-plated lacquered, polished unlacquered, copper-plated matt brushed lacquered as well as chrome-plated. On request, the pendant lamp is also available with a colour temperature of 3,000 Kelvin warm white or 4,000 Kelvin white. Only the pendant lamp with 230-240 volts can be dimmed on site. The 110 - 125 volt version is supplied here as a non-dimmable version.