




Mawa

Wittenberg 4.0 Parquet floor lamp LED

Oberfläche

- noir
- beige
- bleu
- gris
- rouge
- blanc

Technical details

Pays de fabrication	 Allemagne
fabricant	Mawa
concepteur	Jan Dinnebier
concepteur 2	mawa engineering
protection	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
matériel	aluminium, métal
angle du faisceau	38 degrees
couleur de câble	noir
longueur de câble	250 cm
atténuation	intégrée Pushbutton gradateur
Transférabilité	interrupteur au pied
LED	y compris
Indice de rendu des couleurs	95
La température de couleur en Kelvin	2.700 extra blanc chaud
tête de luminaire masse	8 cm
remplacement des ampoules :	sur le site meme
Les performances du système	2 x 12,7 Watt
Flux lumineux total en LM	2.200
répartition de la lumière	directement
Dimensions	H 13 cm B 10 cm L 20 cm

Description

The Mawa Wittenberg 4.0 Parquet floor lamp LED has two half-flush integrated spotlight heads. The lamp heads are individually adjustable, each lamp head can be swivelled by 90 degrees and rotated by 365 degrees. The light is switched on and off via a foot switch on the supply line. The two lamp heads can be dimmed separately and continuously via two push-button dimmers on the lamp. A memory function saves the last selected luminous intensity of the two lamp heads and automatically re-adjusts it when switched on again.

The Wittenberg 4.0 Parquet Floor Lamp LED is available with powder-coated black matt, beige, grey, blue, red or white matt surfaces. On request, this lamp is also offered with a black housing and lamp heads in copper, brass or chrome. As standard, the integrated LEDs have a colour temperature of 2,700 Kelvin extra warm white. On request they are also on offer with 3,000 Kelvin warm white or 4,000 Kelvin white. The colour rendering index of the lamp is Ra 92. On request it is also available with Ra 98, which is closer to natural light (Ra 100). The cable outlet can be selected on the longer or shorter side of the housing. The scope of delivery includes a honeycomb grid with which the light can be emitted without glare.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.