




Mawa

Bullauge 6 pendant mounting with uplight

Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

Pays de fabrication	 Allemagne
fabricant	Mawa
concepteur	Martin Wallroth
protection	IP20
Contenu de la livraison	LED
aptitude de tension	230 - 240 Volt
matériel	verre acrylique, aluminium
longueur de câble	250 cm
réglage de la hauteur	hauteur déterminée
atténuation	gradable avec variateur à coupure de phase et à commande de phase
LED	y compris
répartition de la lumière	directement et indirectement
Dimensions	H 10 cm

Description

The Mawa Bullauge 6 pendant mounting with uplight emits light both upwards and downwards. The pendant light is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, the lamp is made of aluminum in powder-coated white matt. On request it can also be supplied in other RAL colours. The even distribution of the LEDs and the opaque, satinised plexiglass diffuser ensure a very homogeneous, luminous surface at the bottom of the lamp. The three smaller versions of Bullauge 6 pendant mounting with uplight are suspended on three parallel cables, the largest lamp on four parallel cables. The cables have a maximum length of 250 cm and can be shortened if necessary. On request, the lamp is also available with other cable lengths or without uplight.

The Bullauge 6 can be dimmed with a leading edge or trailing edge phase dimmer. On request, it is also available DALI dimmable. It is also offered with a different diameter up to 120 cm on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.