



# Mawa

## Seventies surface-mounted spot light LED dimmable


### Oberfläche

- noir
- blanc

### Farbtemperatur in Kelvin

- 2.700 extra blanc chaud
- 3.000 blanc chaud

## Technical details

<b>Pays de fabrication</b>	 Allemagne
<b>fabricant</b>	Mawa
<b>concepteur</b>	Jan Blieske
<b>concepteur 2</b>	Jan Dinnebier
<b>année</b>	2020
<b>protection</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>aptitude de tension</b>	230 - 240 Volt
<b>matériel</b>	aluminium
<b>angle du faisceau</b>	30 degrees
<b>atténuation</b>	dimmerable sur place avec commande gradateur de phase inverse
<b>Puissance en Watt</b>	25 W
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	>90
<b>tête de luminaire masse</b>	9 cm
<b>remplacement des ampoules :</b>	chez le fabricant / a l'usine
<b>Dimensions</b>	H 22 cm

## Description

The Mawa Seventies surface-mounted spotlight LED has a cylindrical lamp head that can be rotated by 365 degrees and swivelled by 90 degrees. Thanks to its compact design, the ceiling lamp has no visible screw connections. It is a total of 21.6 cm high and has a lamp head with a diameter of 9 cm. The surface-mounted spotlight is available in the powder-coated surfaces white or black matt. It is also available in other RAL colours on request.

The Seventies ceiling spotlight is available with a colour temperature of 2,700 Kelvin extra warm white or 3,000 Kelvin warm white. On request, it is also offered with 4,000 Kelvin white. This lamp can be dimmed on site with a trailing edge phase dimmer. DALI, 1-10 volt or rotary control versions are also available on request. The colour rendering index of the lamp is Ra >90. On request, it is also on offer with Ra >95, which is closer to natural light (Ra 100).

The Seventies surface-mounted spotlight LED has a beam angle of 30 degrees as standard. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 16 or 22 degrees in the field Order Comment.