




# Bover

## Skybell Plus S/1L

### Dimmbarkeit

- 0-10V dimmable
- dimmerable sur place avec commande gradateur de phase inverse

### Technical details

<b>Pays de fabrication</b>	 Espagne
<b>fabricant</b>	Bover
<b>concepteur</b>	Estudi Manel Molina
<b>année</b>	2019
<b>protection</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>aptitude de tension</b>	110 - 240 Volt
<b>matériel</b>	aluminium, Fer
<b>surface</b>	noir
<b>angle du faisceau</b>	36 degrees
<b>réglage de la hauteur</b>	hauteur déterminée
<b>Puissance en Watt</b>	4,2 W
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	93
<b>Flux lumineux en lm</b>	500
<b>La température de couleur en Kelvin</b>	2.700 extra blanc chaud
<b>canopée Dimensions</b>	14 cm
<b>Diamètre de l'ombre</b>	6 cm
<b>remplacement des ampoules :</b>	chez le fabricant / a l'usine
<b>hauteur totale</b>	200 cm

### Description

The lamp shade of the Bover Skybell Plus S/1L pendant lamp has a diameter of 6 cm. The suspension of the lamp can be shortened if necessary. Its total height is 200 cm. The Skybell Plus S/1L has a black lamp shade. The pendant lamp is operated with an integrated LED that has a colour temperature of 2,700 Kelvin extra warm white. The Skybell Plus S/1L can be dimmed on site with a trailing edge phase dimmer or 0-10 volt. The integrated LED is characterised by very good colour rendering with a high colour rendering index of Ra 93. Natural light has a colour rendering index of Ra 100, i.e. the light from this integrated LED is very similar to natural light.