



# Florian Schulz

## Ova

### Version

- messing gepolijst gelakt messing
- messing donker gepolijst gelakt messing
- mat geborsteld gelakt messing
- gepolijst messing afwerking
- messing gepolijst ongelakt
- verchromd messing
- verkoperd messing gelakt
- messing matte verkoperde geborsteld gelakt
- vernikkeld messing
- messing vernikkeld gelakt
- mat geborsteld vernikkeld messing

### Technical details

<b>Land van fabricage</b>	 Duitsland
<b>fabrikant</b>	Florian Schulz
<b>ontwerper</b>	Jens Schump
<b>jaar</b>	2017
<b>bescherming</b>	IP20
<b>Omvang van de levering</b>	LED
<b>voltage geschiktheid</b>	110 - 240 Volt
<b>materiaal</b>	messing
<b>hoogteverstelling</b>	hoogte bepaalbaar
<b>dimmen</b>	dimbaar op locatie met faseafsnijding dimmer
<b>Wattage</b>	96 W
<b>LED</b>	inclusief
<b>Kleurweergave-index</b>	>95
<b>Kleurtemperatuur in Kelvin</b>	2.700 extra warm wit
<b>luifel Dimensions</b>	Breedte 47 cm, hoogte 5 cm
<b>Totale lichtstroom in lm</b>	4.800
<b>lichtverdeling</b>	direct en indirect
<b>totale hoogte</b>	100 - 200 cm
<b>Dimensions</b>	H 4 cm   B 47 cm   L 125 cm

### Omschrijving

The VS Manufaktur Ova is a pendant lamp with an oval lamp body. The length of the lamp is 125 cm, it has a width of 47 cm. The lamp body is 4 cm high. The light is emitted both upwards and downwards. The Florian Schulz Ova is variably determinable in a height of 100 cm to 200 cm. On request, variants with different suspensions are also offered. An LED with a diffuser as well as an power of 60 watts and 2,700 Kelvin extra warm white is integrated. The pendant lamp is available in different surfaces: brass polished lacquered, nickel-plated, matt brushed lacquered, nickel-plated matt brushed, burnished lacquered, dark burnished lacquered, copper-plated, nickel-plated lacquered, polished unlacquered, copper-plated matt brushed lacquered as well as chrome-plated. On request, the pendant lamp is also available with a colour temperature of 3,000 Kelvin warm white or 4,000 Kelvin white. Only the pendant lamp with 230-240 volts can be dimmed on site. The 110 - 125 volt version is supplied here as a non-dimmable version.