




Mawa

Bullauge 6 pendant mounting with uplight

Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

| | |
|-----------------------------|--|
| Kraj produkcji |  Niemcy |
| producent | Mawa |
| projektant | Martin Wallroth |
| ochrona | IP20 |
| zakres dostawy | LED |
| napięcie przydatność | 230 - 240 Volt |
| tworzywo | aluminium, szkło akrylowe |
| długość kabla | 250 cm |
| regulacja wysokości | wysokość ustalona |
| ściemnianie | ściemniające z przycinaniem fazy i ściemniaczem z regulacją fazy |
| LED | łącznie |
| dystrybucja światła | bezpośrednio i pośrednio |
| Dimensions | H 10 cm |

Opis

The Mawa Bullauge 6 pendant mounting with uplight emits light both upwards and downwards. The pendant light is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, the lamp is made of aluminum in powder-coated white matt. On request it can also be supplied in other RAL colours. The even distribution of the LEDs and the opaque, satinised plexiglass diffuser ensure a very homogeneous, luminous surface at the bottom of the lamp. The three smaller versions of Bullauge 6 pendant mounting with uplight are suspended on three parallel cables, the largest lamp on four parallel cables. The cables have a maximum length of 250 cm and can be shortened if necessary. On request, the lamp is also available with other cable lengths or without uplight.

The Bullauge 6 can be dimmed with a leading edge or trailing edge phase dimmer. On request, it is also available DALI dimmable. It is also offered with a different diameter up to 120 cm on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.