



## Cini & Nils

### Acqua 3 lamps with round canopy


#### Oberfläche

- złoto
- srebro
- biały

#### Version

- Downlight
- Uplight

### Technical details

|  |  |
|--|--|
| <b>Kraj produkcji</b>                          |  Włochy |
| <b>producent</b>                               | Cini & Nils  |
| <b>projektant</b>                              | Luta Bettonica   |
| <b>rok</b>                                     | 2014   |
| <b>ochrona</b>                                 | IP20   |
| <b>zakres dostawy</b>                          | LED  |
| <b>napięcie przydatność</b>                    | 230 - 240 Volt   |
| <b>tworzywo</b>                                | aluminium, stal  |
| <b>regulacja wysokości</b>                     | wysokość ustalona  |
| <b>ściemnianie</b>                             | ze sterowanym przełącznikiem, zintegrowanym ściemniaczem                                   |
| <b>LED</b>                                     | Łącznie  |
| <b>Wskaźnik oddawania barw</b>                 | 95   |
| <b>Temperatura barwowa w stopniach Kelvina</b> | 2.800 biała ciepła   |
| <b>baldachim Wymiary</b>                       | 16 cm  |
| <b>wydajność systemu</b>                       | 3 x 5,6 Watt   |
| <b>Całkowity strumień świetlny w lm</b>        | 1.950  |
| <b>wysokość całkowita</b>                      | 200 cm   |
| <b>Dimensions</b>                              | H 86 cm   B 10 cm   L 11 cm  |

### Opis

The Cini & Nils Acqua 3 lamps with round canopy consists of three lamps. The three lights are plugged together and suspended jointly from the round canopy. The lamp is available in the surfaces white, silver matt and gold matt. On request it is also offered in silver leaf or gold leaf. The canopy with a diameter of 16 cm is delivered in the matching surface to the lamp. The Acqua is available in two versions: As an uplight it emits indirect light directed upwards and as a downlight it emits direct light downwards.

The pendant light is regulated with a switch-controlled, integrated dimmer. This means that the light can be dimmed continuously via the normal light switch. No additional cables are required. The dimming function is activated by switching on and off once. The maximum light intensity is reached within seven seconds. To save the desired light intensity, switch on and off again. The set light intensity is saved via a memory function and is automatically selected when the lamp is switched on again. On request, the lamp can also be supplied with a push dimmer on site.

In addition to this Acqua with 3 lights on a round canopy, versions with up to 6 lights are also available on request. The lamp is also available on request with an oval canopy with up to ten lights. The Acqua pendant light can be adjusted in height if required. A decentralisation kit is offered as an accessory, which allows the lamp to be installed independently of a power supply.